

## GET WIRELESS with the Brand New

# DALI ZENSOR AX











### Let the Music Flow!

With the brand new series of active speakers you're freed from the hassle with electronics that's usually associated with a high quality stereo experience.

The DALI ZENSOR AX has a build-in 2 x 50W stereo all digital amplifier that delivers the audio signal to both loudspeakers and is designed to bring out the best from its passive ZENSOR host regardless of the signal type. Feel free to use Bluetooth (Apt-X if your device supports it) or connect an analogue source with a mini-jack or an optical via TOSLink. Connect your TV via the optical input or any type of traditional audio player via the analogue input.

- . HI-FI quality audio without the hassle of bulky electronics
- Classic DALI trademarks Wood Fibre cones and large Soft Dome tweeter
- 2 x 50 Watts fully digital amplifier
- Bluetooth (Apt-X), Optical and analogue inputs
- Subwoofer output

#### Available in:





White



Black

Walnut

#### TECHNICAL SPECIFICATIONS

Frequency Range (+/-3 dB) [Hz] Maximum SPL [dB] Crossover Frequency [Hz] Crossover Principle High Frequency Driver Low Frequency Driver Enclosure Type Continous IEC Amplifier Output [RMS watt] Input Impedance  $[\Omega]$ Input Sensitivity [mV] Connection Input(s) Amplifier Type Maximum digital resolution[bits/KHz] Recommended Placement Input mains Maximum Power Consumption [W] Standby Power Consumption [W] Dimensions (HxWxD) [mm]

Weight [kg/lb]
Accessories Included

#### **ZENSOR 1 AX**

53 - 26,500 2,900 2-way 25 mm soft dome 1 x 51/4 Bass reflex 2x50W 12.6K 300 3.5mm Stereo mini jack, Optical (Toslink) Bluetooth™ Apt-X Sub out Fully digital class D (Open loop type) 24 / 96 Wall/Shelf/Wall Universal mains100-240V 160W <0.5W 274 x 162 x 240 4.6 / 10.1 Mains cable, rubber feet, wall bracket, rubber bumbers remote control, manual. right speaker wire

#### **ZENSOR 5 AX**

43 - 26,500
106
2,400
2-way
25 mm soft dome
2 x 5¼"
Bass reflex
2x50W
12.6K
300
3.5mm Stereo mini jack,
Optical (Toslink)
Bluetooth™ Apt-X
Sub out
Fully digital class D
(Open loop type)
24 / 96
No
Floor
Universal mains 100-240V
160W
<0.5W
840 x 212 x 282
11.0 / 24.3
Mains cable, rubber feet,
spike set, remote control,
manual, right speaker wire







