









<p><b>Product images</b></p>	<div> <div>  </div> <div>  </div> <div>  </div> </div>			
<p><b>Brief description</b></p>	<p>AmbienTone is a flat panel loudspeaker in a modified gypsum plasterboard. It is installed in drywall constructions. In very few work steps. Once connected, fitted and sealed, AmbienTone can be wallpapered over, painted and even plastered over. A coat with a thickness of up to 2 mm will result in only a minimal loss of sound quality.</p>			
<p><b>Handling and installation instructions</b></p>	<p><b>Step 1:</b> Install the metal stand wall. At the corresponding positions, make a frame construction for the AmbienTone panels, so that these can be secured on all sides with screws.</p> <p><b>Step 2:</b> Insert the soundproofing material and cover the metal stand wall with plasterboards. Be sure to connect the AmbienTone panel before inserting it.</p> <p><b>Step 3:</b> Secure the AmbienTone panel on all sides with screws. A functional test is then recommended to check the wall for vibrations.</p> <p><b>Step 4:</b> Fill the gaps and smoothen them.</p> <p><b>Step 5:</b> Complete the wall with a finish of your choice. Of course, the scope of delivery also includes full assembly instructions. The figure below provides an overview.</p> <div>      </div>			
<p><b>Technical data</b></p>	<ul style="list-style-type: none"> <li>Carrier:</li> <li>Size (H x W x D):</li> <li>Weight:</li> <li>System:</li> <li>Version:</li> <li>Power handling:</li> <li>Impedance:</li> <li>Frequency range:</li> <li>Sensitivity:</li> <li>Max. SPL:</li> <li>Dispersion angel:</li> <li>Connection:</li> </ul>	<p>AmbienTone No.4 (60 Watt)</p> <p>12,5mm plasterboard 625 x 500 x 44mm ca. 5,5kg 2-ways</p> <p>60 Watts 6 Ohm 80 Hz–18 kHz 92.5 dB 108 dB H x V 180° x 180° 10m speaker cable</p>	<p>AmbienTone No.1 (40 Watt)</p> <p>12,5mm plasterboard 700 x 500 x 44mm ca. 5,5kg 2- ways</p> <p>40 Watts 4 Ohm 80 Hz–18 kHz 85 dB (1 Watt/ 1m) 102 dB H x V 180° x 180° 10m speaker cable</p>	<p>AmbienTone No.1 (100V)</p> <p>12,5mm plasterboard 700 x 500 x 44mm ca. 5,8kg 2- ways 100 Volt 25 Watts ( 6/12/20/25 Watts to grip)</p> <p>80 Hz–18 kHz 85 dB (1 Watt/ 1m) 102 dB H x V 180° x 180° 10m speaker cable</p>



Overview of items	AMBIENTONE NO.4 & NO.1			
	Item-no.	Designation	Unit	SRP
	0025004	AmbienTone No. 4 In-Wall-speaker; 2-way; 60W; 6 Ohm	1 pc	1318,90
	0025004100	AmbienTone No. 4 In-Wall-speaker; 2-way; 100 Volt	1 pc	1483,90
	0025001	AmbienTone No. 1 In-Wall-speaker; 2-way	1 pc	1208,90
	0025001100	AmbienTone No. 1 In-Wall-speaker; 2-way; 100 Volt	1 pc	1318,90