

AMBIENTONE NO. 6 | FOR INSTALLING IN SOLID WALLS



Product images







Brief description

AmbienTone No.6 is a speaker module for invisible integration in solid walls. The flat-panel speaker constructed according to the principle of the bending wave converter. The module is embedded into a niche constructed in the wall and plastered over completely. Available as an option in a 100 V model.

Note: the design of the AmbienTone No.6 module ensures an extremely high decoupling between the membrane surface and the surrounding surface of the wall. However, structure-borne sound which spreads through the walls can still occur, depending on the construction and workmanship of the masonry. Before installing the panel, check the static function of the wall you would like to use.

Technical data

- Carrier: Foam membrane
 Size (H x W x D): 435x 570 x 45 mm
- Weight: ca. 3,5 kg
 System: 2-ways
- Power handling: 40 WattsImpedance: 4 Ohm
- Frequency range: 80 Hz–18 kHz
 Sensitivity: 85 dB (1 Watt / 1m)*
- Dispersion angel: H x V 180° x 180°
 Connection: 10 m speaker cable

Overview of items

AMBIENTONE NO.6			
Item-no.	Designation	Unit	SRP
0025006	AmbienTone No. 6 module for brick wall; 2-way; 40W; 4 Ohm	1 pc	1208,90

^{*} For 2 mm plaster approx. -2 dB