

## LINC 2X2.5

Screened Loudspeaker cable


Gauge: 2x2.5mm<sup>2</sup> / AWG 13

Rev.date: 2022-08-30

Customs tariff no: 8544499390

Country of origin: Sweden

- Screened - less pick-up noise
- Low inductance
- Double insulated, approved for 100V systems
- Tin plated - Corrosion resistant



### LINC 2x2.5 - screened

Supra Linc is an evolution of the Supra round two part cable Rondo and the already low level of magnetic fields, thanks to the short pitch twinning. Supra Linc have been supplemented with a shield blocking the electrical fields, especially the pick-up of malignant RFI (radio frequency interference, whether it is analogue or digital). Its low inductance properties allows for transient transparency. Linc is short for Low Interaction Concept, is flexible to install making it suitable for e.g. permanent in-wall installations in conduits. The result is immediately lowered noise floor and increased dynamics of the Hi-Fi system. Especially the so called micro dynamics; tiny, tiny notes, phrasing, the small differences how hard the drum is hit, in fact all the small discrepancies making the music come alive and not sounding artificial will appear and suddenly stand out from a pitch black background, free from noise, a truly remarkable discovery for most music lovers.

The drain-wire/screen should be connected to the earth screw/chassis of the amplifier/negative speaker terminal only, cut the screen at the speaker end.

### CONSTRUCTION

|                       |  |
|-----------------------|--|
| Conductor (x2):       | Tin plated OFC-wire 320x0.10 mm                |
| Diameter:             | 2.3 mm   |
| Cross section Area:   | 2x2.5mm <sup>2</sup> / AWG 13                  |
| Insulation:           | Red + & Black -                                |
| Insulation thickness: | 0.7 mm   |
| Screen:               | Alu/PET foil, 100%                             |
| Screen connection:    | Tin plated OFC drain wire 19x0.127mm           |
| Jacket:               | PVC GA78, round                                |
| Jacket thickness:     | 1.5 mm   |
| Diameter:             | 8.1 mm   |
| Colour:               | Iceblue (other colours upon order)             |
| Marking:              | SUPRA LINC 2x2.5 + Made in Sweden + Meter mark |
| Weight:               | 94 kg/km                                       |
| Packing:              | Bobbin 100m (other lengths upon order)         |

#### Earth/Screen connection.

The earth conductor should be connected in the source end only (amplifier side) to:

1. Earth terminal at the amp (if available)
2. Connect to any of the amp chassis screws.
3. Negative speaker out terminal



### ELECTRICAL SPECIFICATION

|                |            |
|----------------|------------|
| Resistance:    | 6.8 ohm/km |
| Inductance:    | 0.40 uH/m  |
| Rated voltage: | 100V       |

| PRODUCT              | Qty  | Part.no    | EAN-13        | E-no    |
|----------------------|------|------------|---------------|---------|
| LINC 2X2.5 BLUE B100 | 100M | 1000000180 | 7330060000140 | 4866583 |