

MONITOR SE





DISCOVER SUPERIOR AUDIO PERFORMANCE, WITHOUT THE COST.

The stylish and affordable new Monitor SE Series is the perfect introduction to the world of highperformance audio. Sure it's packed with state-ofthe-art technology, the kind of stuff only found on speakers that cost much more. But more important, the new Monitor SE Series is part of the Paradigm family of high performance loudspeakers, and just like all Paradigm loudspeakers, it's engineered to change the way you think and feel about your entertainment.

ADVANCED TECHNOLOGY INCLUDES:

- Poly Cones with inverted caps, reverse roll surrounds and X-PAL™ Tweeters.
- Perforated Phase Alignment (PPA™) Lens smooths extended high frequency response for incredible detail.
- Computer optimized second-order crossovers. engineered for seamless dynamic integration.



Gloss White

Matte Black











	MONITOR © 8000F	MONITOR © 6000F	MONITOR SE 3000F	MONITOR © 2000C	MONITOR SE ATOM
Design	5-driver, 3-way bass reflex floorstanding	5-driver, 3-way bass reflex floorstanding	4-driver, 3-way bass reflex floorstanding	3-driver, 2-way bass reflex center channel	2-driver, 2-way bass reflex bookshelf
Crossover	2nd-order electro- acoustic at 2.5kHz (tweeter/mid) and 550Hz (mid/woofers)	2nd-order electro- acoustic at 3.0 kHz (tweeter/mid) and 800Hz (mid/woofers)	2nd-order electro- acoustic at 3.0kHz (tweeter/mid) and 800Hz (mid/woofers)	2nd-order electro- acoustic at 2.0kHz	2nd-order electro- acoustic at 2.3kHz
High Frequency Driver	1" (25mm) X-PAL™ dome, ferro-fluid damped/ cooled, Perforated Phase- Aligning (PPA™) Lens	1" (25mm) X-PAL™ dome, ferro-fluid damped/ cooled, Perforated Phase- Aligning (PPA™) Lens	1" (25mm) X-PAL™ dome, ferro-fluid damped/ cooled, Perforated Phase- Aligning (PPA™) Lens	1" (25mm) X-PAL™ dome, ferro-fluid damped/ cooled, Perforated Phase- Aligning (PPA™) Lens	1" (25mm) X-PAL™ dome, ferro-fluid damped/ cooled, Perforated Phase- Aligning (PPA™) Lens
Midrange Driver	6-1/2" (165mm) mineral- filled polypropylene cone/inverted dust cap/downroll surround	5-1/2" (140mm) mineral- filled polypropylene cone/inverted dust cap/downroll surround	5-1/2" (140mm) mineral- filled polypropylene cone/inverted dust cap/downroll surround	N/A	N/A
Bass/Midrange Driver	N/A	N/A	N/A	Two 5-1/2" (140mm mineral-filled polypropylene cones/ inverted dust cap/ downroll surround	5-1/2" (140mm) mineral- filled polypropylene cone / inverted dust cap / downroll surround
Bass Driver	Three 8" (203mm) mineral-filled polypropylene cones/ inverted dust cap / downroll surrounds	Three 5-1/2" (140mm) mineral-filled polypropylene cones/ inverted dust cap/ downroll surrounds	Two 5-1/2" (140mm) mineral-filled polypropylene cones/ inverted dust cap/ downroll surrounds	N/A	N/A
Low Frequency Extension	35 Hz (DIN)	49Hz (DIN)	51Hz (DIN)	52Hz (DIN)	45Hz (DIN)
Frequency Response (On Axis)	+/- 3dB from 40Hz — 21kHz	+/- 3dB from 40Hz — 21kHz	+/- 3dB from 42Hz — 21kHz	+/- 3dB from 64Hz — 21kHz	+/- 3dB from 55Hz — 21kHz
Frequency Response (30°)	+/- 3dB from 40Hz — 17kHz	+/- 3dB from 40Hz — 17kHz	+/- 3dB from 42Hz — 17kHz	+/- 3dB from 64Hz — 17kHz	+/- 3dB from 55Hz — 17kHz
Sensitivity - Room	95 dB	93 dB	91 dB	93 dB	89 dB
Sensitivity - Anechoic	92 dB	90 dB	88 dB	90 dB	86 dB
Suitable Amplifier Power Range	15-150W	15-130W	15-130W	15-100W	15-100W
Maximum Input Power	150 Watts	100 Watts	100 Watts	50 Watts	50 Watts
Impedance	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 8 ohms
Overall Dimensions (h x w x d)	45-7/8" x 11-3/4" x 17-11/16" (116.5 x 29.8 x 42.4cm)	41-1/4" x 9" x 14-1/8" (105cm x 23cm x 36cm)	39-1/2" x 9" x 11-1/8" (100.4cm x 23cm x 28cm)	7-1/4" x 19-3/4" x 11-1/8" (18.3cm x 50cm x 28cm)	12-3/4" x 7-1/8" x 11" (32cm x 18cm x 27cm)
Weight	69 lbs/31.2kg each	44lb (19.9kg) each	35lb (15.8kg) each	19lb (8.6kg) each	12lb (5.4kg) each
Finish	Matte Black, Gloss White	Matte Black, Gloss White	Matte Black, Gloss White	Matte Black, Gloss White	Matte Black, Gloss White

Specifications are subject to change without notice. Stands are sold separately.

Dimensions include grille and terminal posts for all models. Includes feet for Monitor SE 8000F, Monitor SE 6000F and Monitor SE 3000F. Includes isolation pads for center channel and bookshelf speakers.

