



Movie 135

Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2-way closed system Center: 2-way closed system Surround: 2-way closed system Subwoofer: Bandpass system
Nom. /Music power handling	Front: 100 watts Center: 100 watts Surround: 100 watts
Musical output	Subwoofer: 120 watts
SPL (1 watt/1m)	85 dB
Frequency response	Front: 120...25.000 Hz Center: 120...25.000 Hz Surround: 120...25.000 Hz Subwoofer: 33...140 Hz
Crossover frequency	Front: 5.000 Hz Center: 5.000 Hz Surround: 5.000 Hz Subwoofer: 80...140 Hz (adjustable)
Woofer	Front: 1 x 80 mm (3.2"), Aluminum Center: 2 x 80 mm (3.2"), Aluminum Surround: 1 x 80 mm (3.2"), Aluminum Subwoofer: 1 x 200 mm (8"), Aluminum
Tweeter	Front: 1 x 15 mm (1"), aluminum Center: 1 x 15 mm (1"), aluminum Surround: 1 x 15 mm (1"), aluminum
Nominal Impedance	4...8 ohms
Special Features	Front: Wall brackets included Center: Wall brackets included Surround: Wall brackets included Subwoofer: Adjustable crossover frequency Adjustable bass level SC-technology 5 years warranty for front-,center- and rear- speakers 2 years warranty for subwoofer
Dimensions (WxHxD)	Front: 8.9 x 11.6 x 10.6 cm (3.5 x 4.6 x 4.2) Center: 19.6 x 8.9 x 10.6 cm (7.7 x 3.5 x 4.2) Surround: 8.9 x 11.6 x 10.6 cm (3.5 x 4.6 x 4.2) Subwoofer: 24 x 41 x 42 cm (9.5 x 15.9 x 16.7)
Weight	Front: 0.8 kg Center: 1.4 kg Surround: 0.8 kg Subwoofer: 9.8 kg
Power consumption	0,42 Watt
Available accessories	Loudspeaker stand LS 90.2

Carton Content	Canton Movie 135 Wallmounts Equipment feet Manual
Packaging	64 x 48,5 x 32 cm (25,2" x 19,1" x 12,6")