



Movie 165

Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2-way closed system Center: 2-way closed system Surround: 2-way closed system Subwoofer: Bandpass system
Nom. /Music power handling	Front: 120 watts Center: 120 watts Surround: 120 watts
Musical output	Subwoofer: 120 Watts
SPL (1 watt/1m)	85 dB
Frequency response	Front: 120...25.000 Hz Center: 120...25.000 Hz Surround: 120...25.000 Hz Subwoofer: 33...140 Hz (adjustable)
Crossover frequency	Front: 5.000 Hz Center: 5.000 Hz Surround: 5.000 Hz Subwoofer: 80...140 Hz (adjustable)
Woofers	Front: 1 x 80 mm (3.2"), Aluminum Center: 2 x 80 mm (3.2"), Aluminum Surround: 1 x 80 mm (3.2"), Aluminum Subwoofer: 1 x 200 mm (8"), Aluminum
Tweeter	Front: 1 x 15 mm (1"), aluminum Center: 1 x 15 mm (1"), aluminum Surround: 1 x 15 mm (1"), aluminum
Nominal Impedance	4...8 ohms
Special Features	Front: Wall brackets included Center: Wall brackets included Surround: Wall brackets included Subwoofer: Adjustable crossover frequency Adjustable bass level SC-technology Center: Magnetically shielded Surround: Polymer protection Wall brackets included Subwoofer: Downfire Woofer Adjustable phase limiter Adjustable crossover frequency 5 years warranty for front-,center- and rear- speakers 2 years warranty for subwoofer
Dimensions (WxHxD)	Front: 10,8 x 16 x 12,1 cm (4.3 x 6.3 x 4.8) Center: 29 x 10,8 x 12,1 cm (11.4 x 10.8 x 4.8) Surround: 10,8 x 16 x 12,1 cm (4.3 x 6.3 x 4.8) Subwoofer: 24 x 41 x 42 cm (9.5 x 15.9 x 16.5)

Weight	Front: 1.2 kg Center: 1.9 kg Surround: 1.2 kg Subwoofer: 9.8 kg
Power consumption	0,42 Watt
Available accessories	Loudspeaker stand LS 90.2
Carton Content	Canton Movie 165 Wallmounts Equipment feet Manual
Packaging	67,5 x 48,5 x 32 cm (26,6" x 19,1" x 12,6")