



Movie 265

Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2-way closed system Center: 2-way closed system Surround: 2-way closed system Subwoofer: Bandpass system
Nom. /Music power handling	Front: 120 watts Center: 120 watts Surround: 120 watts
Musical output	Subwoofer: 120 watts
SPL (1 watt/1m)	85 dB
Frequency response	Front: 120...25.000 Hz Center: 120...25.000 Hz Surround: 120...25.000 Hz Subwoofer: 33...140 Hz (adjustable)
Crossover frequency	Front: 5.000 Hz Center: 5.000 Hz Surround: 5.000 Hz Subwoofer: 80...140 Hz (adjustable)
Woofer	Front: 2 x 80 mm (3.2"), Aluminum Center: 2 x 80 mm (3.2"), Aluminum Surround: 2 x 80 mm (3.2"), Aluminum Subwoofer: 1 x 200 mm (8"), Aluminum
Tweeter	Front: 1 x 15 mm (1), Aluminium Center: 1 x 15 mm (1), Aluminium Surround: 1 x 15 mm (1"), Aluminium
Nominal Impedance	4...8 ohms
Special Features	Front: Wall brackets included Center: Wall brackets included Surround: Wall brackets included Subwoofer: Adjustable crossover frequency Adjustable bass level SC-technology 5 years warranty for front-,center- and rear- speakers 2 years warranty for subwoofer
Dimensions (WxHxD)	Front: 8,9 x 19,6 x 10,6 cm Center: 19,6 x 8,9 x 10,6 cm Surround: 8,9 x 19,6 x 10,6 cm Subwoofer: 24 x 41 x 42 cm
Weight	Front: 1.8 kg Center: 1.8 kg Surround: 1.8 kg Subwoofer: 9.8 kg
Power consumption	0,42 Watt

Carton Content	Canton Movie 265 Wallmounts Equipment feet Manual
Packaging	72 x 48,5 x 32 cm (28,3" x 19,1" x 12,6")