



Movie 95

| | |
|----------------------------|---|
| Type | Home-Cinema-System with active subwoofer system |
| Engineering Principle | Front: 2-way closed system Center: 2-way closed system Surround: 2-way closed system Subwoofer: Bandpass system |
| Nom. /Music power handling | Front: 100 watts Center: 100 watts Surround: 100 watts |
| Musical output | Subwoofer: 140 watts |
| SPL (1 watt/1m) | 85 dB |
| Frequency response | Front: 120...25.000 Hz Center: 120...25.000 Hz Surround: 120...25.000 Hz Subwoofer: 33...140 Hz (adjustable) |
| Crossover frequency | Front: 5.000 Hz Center: 5.000 Hz Surround: 5.000 Hz Subwoofer: 80...140 Hz (adjustable) |
| Woofer | Front: 1 x 80 mm (3.2"), Aluminum Center: 2 x 80 mm (3.2"), Aluminum Surround: 1 x 80 mm (3.2"), Aluminum Subwoofer: 1 x 200 mm (8"), Aluminum |
| Tweeter | Front: 1 x 15 mm (1"), aluminum Center: 1 x 15 mm (1"), aluminum Surround: 1 x 15 mm (1"), aluminum |
| Nominal Impedance | 4...8 ohms |
| Special Features | Center: Wall brackets included Surround: Coax system Wall brackets included Subwoofer: Adjustable crossover frequency Adjustable bass level SC-technology 5 years warranty for front-,center- and rear- speakers 2 years warranty for subwoofer |
| Dimensions (WxHxD) | Front: 8.9 x 9 x 10.6 cm (3.5 x 3.5 x 4.2) Center: 19.6 x 8.9 x 10.6 cm (7.7 x 3.5 x 4.2) Surround: 8.9 x 9 x 10.6 cm (3.5 x 3.5 x 4.2) Subwoofer: 24 x 41 x 42 cm (9.5 x 15.9 x 16.7) |
| Weight | Front: 0.6 kg Center: 1.3 kg Surround: 0.6 kg Subwoofer: 9.8 kg |
| Power consumption | 0,42 Watt |
| Available accessories | Loudspeaker stand LS 90.2 |

| | |
|----------------|---|
| Carton Content | Canton Movie 95 Wallmounts Equipment feet Manual |
| Packaging | 64 x 48,5 x 32 cm (25,2" x 19,1" x 12,6") |